

2.8C

**FAT TRUCK®**  
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



**Zeal Motor Inc.**

90 Blvd de l'Aéroport, Bromont  
Quebec, Canada J2L 1S9

579.319.0060

[sales@zealmotor.com](mailto:sales@zealmotor.com)

[WWW.FATTRUCK.COM](http://WWW.FATTRUCK.COM)

# 2.8C

## SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		CAB OPTIONS	
Payload	2200 lb (1000 kg)	Make	Caterpillar	Front & Rear	FAT TRUCK® LGP 1640 x 640 x 610	Custom color	
Passengers capacity	8 (2 front + 6 rear)	Model	C2.2 Turbo diesel	Pressure	0.5 to 4 lb/po <sup>2</sup> (0.035 to 0.28 kg/cm <sup>2</sup> )	Air conditioning	
Maximum speed on land	25 mph (40 km/h)	Emission standards	Tier 4 final (no DPF)	Pressure control	Preset automatic pressure control	Basic brush guard	
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders	4 cylinders	FUEL SYSTEM		Additional Brush guard(s)	
Maximum uphill & downhill	35°/ 70%	Displacement	135 po <sup>3</sup> (2.22 L)	Capacity	18.5 US Gal (70 L)	Roof rack with rear ladder	
Maximum sidehill	22°/ 40%	Horsepower @ 2800 RPM	67 hp (50 kW)	Average fuel autonomy	10 h	Exterior mirrors	
Turning radius	0°	Torque @ 1400 RPM	153 lb-pi (208 N-m)	STANDARD EQUIPMENT		Rear seats with 2-points safety belts	
Shipping weight	5400 lb (2443 kg)	Cooling System	Liquid cooled	Doors	Lockable	3-points seat belts	
Ground pressure fully loaded	1.6 lb/po <sup>2</sup> (0.11 kg/cm <sup>2</sup> )	ELECTRICAL		Operator seats	2 front seats with 3-points seat belts	Directional light with remote control	
SAFETY FEATURES		Voltage	12 V	Windows	Sliding side windows	Front and rear light bar	
ROPS	ISO 3471	Alternator capacity	160 A	Lights	Front, brakes, position, flashers, dome	Bluetooth radio with speakers	
EPA	TIER 4 Final	Battery capacity	960 CCA	Heating	Heater/Defroster	LED beacon light	
Brakes	Automatic safety brake	Battery type	AGM	Horn	Electric	Back up camera	
DIMENSIONS		TRANSMISSION		Ingress	Retractable ladders with grab handles	Back-up alarm	
Height	101 in (2565 mm)	Type	Hydrostatic	Standard color	Red or white	Electronic inclinometer	
Length	146.5 in (3720 mm)	Final drive	Carbon fiber synchronous belts	Fire extinguisher	2.5 lbs. ABC	Roof hatch	
Width	100 in (2540 mm)	BRAKES		Bilge pump		4 ventilation fans	
Ground clearance	20.7 in (526 mm)	Brakes	Positive deceleration through hydrostatic transmission	Cup holders		OPTIONS	
CONTROLS		Park brakes	Brake disc applied pressure released	First aid kit		Engine & hydraulic heater 110 V	
Controller	Microprocesseur			Lockable fuel cap		Hydraulic capstan kit	
Steering	Joystick			Front and rear bumpers		Variable cooling fan for engine	
Display	Color display			Operator & Maintenance manual		4-way camera system	
WARRANTY				Spare Parts catalog (on USB flash drive)		Hot sticks storage tubes	
Limited 1 year / 1000 hours (Which ever comes first)						Blanket over engine compartment	
						Vehicle remote control	
						Winch	
						Additional battery	
						Cold weather Kit	
						Hitch	
						Trailer / Amphibious trailer	
						Front and rear D-rings	
						Winch ready 12 V front & rear	
						Side LED bar	
						Wheel Pods™	

